

DRAWING ISO 207 REV. "Q"

TABLE II - DIMENSIONS

CABLE ENTRY	F	N	S	SPRING
01	1.69	0.442	(2) 0.250	ISO100
02	1.78	0.530	(2) 0.250	ISO100
03	1.85	0.619	(2) 0.500	ISO100
04	1.97	0.707	(2) 0.500	ISO100
05	2.12	0.795	(2) 0.500	ISO100
06	2.20	0.875	(2) 0.500	ISO51
07	2.235	1.000	(2) 0.500	ISOEL1
08	2.450	1.125	(2) 0.500	ISOE15
09	2.575	1.250	(2) 0.500	ISOE15
10	2.700	1.375	(2) 0.500	ISOE15
11	2.825	1.500	(2) 0.500	ISOGV3
12	2.950	1.625	(2) 0.500	ISO13
13	3.075	1.750	(2) 0.750	ISO13
14	3.200	1.875	(2) 0.750	ISO14
15	3.325	2.000	(2) 0.750	ISO15

ISODYNE INC.

7706 E. OSIE – WICHITA, KS. 67207

U.S. PATENT # 5,769,665 & 6,918,785

CAGE CODE # 031M6

D SUB BACKSHELL, EMI / RFI
SPRING BAND